










TRASEU CONDUCTA

MATERIALE FOLOSITE

<b>MATERIAL CONDUCTA</b> Teava trasa Ø610 x 11mm, L 360N, PSL 2 conf. SR EN ISO 3183:2013 - teava preizolata cu PE, tip N - v conf. DIN 30670 cu grosimea de 3.2mm conf. SR EN ISO 21809-1:2011; - mansoane termocontractile tip C50L la imbinari conf. SR EN 12068:2002		<i>Lungime reala conducta Ø24" proiectata L= 431.00m, din care: 393.00m cd. izolata cu PE 38.00 m cd. pentru curbe</i>				CANTITATI	
<b>TRAVERSARI APE, DRUMURI, CF IN TUB PROTECTOR</b> Teava tub protectie Ø813 x 10mm, sudata elicoidal L 245N,PSL 1 conf. SR EN ISO 3183:2013		1buc. x 46.00 m (pich. 16 - 24)				393.00m	
<b>SCHIMBARI DE DIRECTIE CU CURBE</b> Teava CMF Ø610 x 12.5mm, Rc 5.2, L 360N		<i>Lungime teava pentru curbe L= 38.00m</i>				46.00m	
in plan orizontal	stanga	1 x 70° (pich. 2)	1 x 45 ° (pich. 4)	1 x 90° (pich. 14)	1 x 90° (pich. 27)	4 buc.	
	dreapta						
in plan vertical	urcare					2 buc.	
	coborare						
<b>PRESETUPE</b> Ø32" / Ø24"		2 buc. (pich. 16 - 24)				49 buc.	
<b>INELE DISTANTIERE</b> - tip ALTA M/N Ø32" / Ø24" amplasate la o distanta de 1.0m intre ele		49 buc.					
<b>PROTECTIE CATODICA</b>		 priza de potential cu anodi, la cuplare pichet nr. 1		 priza de potential cu anodi pichet nr. 24		2 buc.	
<b>LUCRARI SI INSTALATII AUXILIARE</b>		intre pich. 16 - 24 					
<b>CLASA DE SUDURA</b>		clasa I-a de calitate a imbinarilor sudate conform SR EN 14163:2004; control cu R.P. la traversare DJ 226: 100% sudurile de pozitie, cuplari; in fir curent 25%				1 buc. - c. m. scurgeri 1 buc. - d.aerisire	
<b>SAPATURA</b>		sapatura mecanizata 80%, sapatura manuala 20%, adancime sant 1.41 m, latime sant 2.00 m in fir continuu					
<b>CULOAR DE LUCRU</b>		20.00 m					
<b>PROBE PRESIUNE</b>		1) proba de rezistenta cu apa la 80 bar timp de min. 1 ora; 2) proba de etanseitate finala cu apa la 70.4 bar timp de min. 8 ore.					
<b>ARMATURI</b> Flanse, robineti si elemente electroizolante		- Robinet cu sertar pana PN 64, DN 600 - 2 buc. (pichet 1, 28) - Flansa PN 64, DN 600 - 4 buc. (pichet 1, 28)					
<b>BORNE SCHIMBARE DIRECTIE</b>		 pichet 1	 pichet 2	 pichet 4	 pichet 14	 pichet 27	 pichet 28
						6 buc.	

Verificator/ Expert	Nume	Semnatura	Cerinta	Referat / Expertiza Nr. / Data	
S.C. SNIF PROIECT S.A. Targoviste Numar de inmatriculare J15/925/2005			Beneficiar: CONPET S.A. PLOIESTI		Pr. nr. 343/2017
Specificatie	Nume	Semnatura	Scara:	"Inlocuire conducta titei Ø 24" Constanta - Midia, in zona Pod Navodari - inceput traseu aerian in lungime de 405m "	Faza PT+CS+DE
Sef proiect	Ing. Costea Paul				
Desenat	Ing. Radu Florin		Data: 2017	SCHEMA DE MONTAJ CONDUCTA Ø24 " PROIECTATA	Pl. nr. 24
Proiectat	Ing. Costea Paul				